



# XIS-6545DV



# **PRODUCT HIGHLIGHTS**

**Dual 180kV Generators** 

High Image Resolution with 24-Bit Color

**Enhanced Material Discrimination** 

Windows Operating System with Intel® Core™ Processor

Real-Time Diagnostics

Picture Perfect Image Analysis

The XIS-6545DV™ is an advanced X-Ray Inspection System (XIS) with the most power available for a system with its tunnel size. The dual generators are offset by 90°, providing two upward, diagonal views of scanned objects. Each view can be manipulated independently, with separate image filters. This unique configuration allows operators to inspect bags in depth and gives the system a compact footprint well-suited to confined spaces.

With Astrophysics' best-in-class software, operators are able to utilize colorful, high-contrast filters to identify materials, recognize objects, and isolate threats with better speed and accuracy. The high-quality images enable greater throughput, making the XIS-6545DV an ideal solution for high-volume checkpoints requiring power, reliability, and efficiency.

The Astrophysics XIS-6545DV is designed and assembled in the United States to the highest quality standards. For nearly twenty years, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners.

### **GENERAL SPECIFICATIONS**

Tunnel Size: 65.7 cm x 45.1 cm (WxH) 25.8" x 17.7"

 $213.3 \text{ cm} \times 101.6 \text{ cm} \times 129.0 \text{ cm}$ Dimensions:1 83.97" x 40.0" x 50.81" (LxWxH)

Net Weight:1 800 kg (1760 lbs) Shipping Weight:1 1100 kg (2425 lbs)

Conveyor Speed: 23 cm/s (45 ft/min) Forward or Reverse

Conveyor Height: 69.1 cm (27.2") from Floor

Conveyor Capacity: 165 kg (364 lbs) Evenly Distributed Load

### **TECHNICAL**

Wire Resolution 41 AWG Typical, 40 AWG Standard Steel Penetration:2 41 mm Typical, 39 mm Standard

# X-RAY GENERATOR & IMAGE PERFORMANCE

Voltage: Dual 180kV, Operating at 165kV

Tube Current: Dual 1.2 mA

Cooling: Sealed Di-Electric Oil Bath with Forced Air Duty Cycle: 100%, No Warm-Up Procedure Required

Beam Direction: Diagonally Upward Shooters

### **COMPUTER & VIDEO**

Platform: Windows® OS 4 GB RAM Memory:

1 TB HDD, 240 GB SSD Storage Capacity:

Backup: Uninterruptible Power Supply (UPS)

(Computer Operation)

Display Type: Dual 19" Flat Panel Color Monitors Display Resolution: 1280 x 1024: 24 Bit/Pixel Color

### **ENVIRONMENTAL**

Operating Temperature:  $0^{\circ}$ C to  $40^{\circ}$ C \  $32^{\circ}$ F to  $104^{\circ}$ F Storage Temperature: -20°C to 60°C \ -4°F to 140°F Humidity: Up To 95% Non-Condensing

# **ELECTRICAL**

System Power: 110 VAC +/- 10% 50/60Hz, 20 Amp Max 220VAC +/- 10% 50/60Hz, 15 Amp Max

# **HEALTH & SAFETY**

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40)

Typical radiation leakage is less than 0.1 mR/hr

(Leakage less than 0.5 mR/hr permitted by U.S. Federal Standards)

### STANDARD FEATURES

6 Color Imaging

Color and Black/White Imaging

Geometric Image Distortion Correction High Penetration Function Organic/Inorganic Imaging

Picture Perfect Pseudo Color

Real-Time Image Manipulation

Reverse Monochrome

Atomic Z-Number Measurement Material Discrimination

9 Quadrant Zoom Continuous Scanning Continuous Zoom Up to 64x Vertical Zoom Panning

Auto Image Archiving Image Review Save Image (RGB)

Image Annotation JPEG Conversion Print Image Capable

Multi-Tier Accessibility Network Ready

Real-Time Self Diagnostics

Baggage Counter

### **OPTIONAL FEATURES<sup>3</sup>**

Barcode Scanning Density Alert Local Language Safe Passage®

Computer Based Training Screener Assist Software

Test Case

Threat Image Projection (TIP) Software

24" Flat Panel Monitor

**Custom Paint** Environmental Kit Entry/Exit Roller Tables Footmat Operator Interlock

Heavy Duty Casters Mobility Kit Radiation Meter

Remote Workstation Configuration

Sloped Conveyor











ISO 9001: Certified

Weight and dimensions of the system may vary depending on customization.

<sup>2</sup>As tested on Astrophysics Inc. Test Piece.

<sup>3</sup>Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information

Due to continued product research and development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice.

Astrophysics HQ +1.909.598.5488

Astrophysics - DC +1.202.350.9740

Astrophysics - HOUSTON +1.713.357.5132

Astrophysics - EMEA +961.9.832.500/1/2

Astrophysics - INDIA +91.11.41709990

Astrophysics - ASIA +63.2.546.1741