







PRODUCT HIGHLIGHTS

Dual View X-Ray Generators

Enhanced Material Discrimination

High Image Resolution

Real-Time Diagnostics

Minimal System Profile

The XIS-7858DVS[™] is a dual-view X-Ray Inspection System (XIS) with a minimal system profile, designed for screening small-to-medium objects in confined spaces at airports, logistics centers, government buildings, industrial sites, and military bases.

The dual generators provide two views of scanned objects, diagonally from below and horizontally from the side. Each perspective can be manipulated independently on separate monitors, allowing operators to examine an object simultaneously in different screening modes. This unique configuration produces sharper images while also enabling the system to function inside a narrow frame.

With Astrophysics best-in-class imaging software, the XIS-7858DVS allows operators to make quick, detailed inspections of complex bags and parcels. Superior imaging ensures higher throughput, making it the ideal solution for high-traffic sites that require a smaller footprint and powerful protection from weapons, explosives, and contraband.

The Astrophysics XIS-7858DVS is designed and assembled in the United States to the highest quality standards. For nearly twenty years, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners.

GENERAL SPECIFICATIONS

Tunnel Size: 77.8 cm x 57.9 cm (WxH) 30.6" x 22.8"

Dimensions:1 259.7 cm x 134.6 cm x 147.3 cm

102.2" x 53.0" x 58.0" (LxWxH) Net Weight:1 1200 kg (2646 lbs) 1500 kg (3307 lbs) Shipping Weight:1

23 cm/s (45 ft/min) Forward or Reverse Conveyor Speed:

Conveyor Height: 73 cm (28.7") from Floor

Conveyor Capacity: 165 kg (364 lbs) Evenly Distributed Load

TECHNICAL

Wire Resolution: 40 AWG Typical, 38 AWG Standard Steel Penetration:2 39 mm Typical, 37 mm Standard

X-RAY GENERATOR & IMAGE PERFORMANCE

Voltage: Dual 180kV, Operating at 165kV

Tube Current: Dual 1.2 mA

Cooling: Sealed Di-Electric Oil Bath with Forced Air Duty Cycle: 100%, No Warm-Up Procedure Required Beam Direction: Diagonally Upward, Horizontally Sideward

COMPUTER & VIDEO

Platform: Windows® OS Memory: 4 GB RAM

Storage Capacity: 1TB HDD, 240 GB SSD

Uninterruptible Power Supply (UPS) Backup:

(Computer Operation)

Dual 19" Flat Panel Color Monitors Display Type: 1280 x 1024; 24 Bit/Pixel Color Display Resolution:

ENVIRONMENTAL

Operating Temperature: 0°C to 40°C / 32F to 104F -20°C to 60°C / -4°F to 140°F Storage Temperature: Humidity: Up to 95% Non-Condensing

ELECTRICAL

110 VAC +/- 10% 50/60Hz, 20 Amp Max System Power:

220 VAC +/- 10% 50/60Hz, 15 Amp Max

HEALTH & SAFETY

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40)

Typical radiation leakage is less than 0.1 mR/hr

(Leakage less than 0.5 mR/hr permitted by U.S. Federal Standards)

STANDARD FEATURES

6 Color Imaging

Color and Black/White Imaging

Geometric Image Distortion Correction High Penetration Function Organic/Inorganic Imaging

Picture Perfect Pseudo Color

Real-Time Image Manipulation

Reverse Monochrome

Atomic Z-Number Measurement

Material Discrimination

9 Quadrant Zoom Continuous Scanning Continuous Zoom Up to 64x Vertical Zoom Panning

Auto Image Archiving Image Review Save Image (RGB)

Image Annotation JPEG Conversion Print Image Capable

Multi-Tier Accessibility Network Ready

Real-Time Self Diagnostics

Baggage Counter

OPTIONAL FEATURES³

Density Alert Local Language

Safe Passage® Computer Based Training Screener Assist Software

Threat Image Projection (TIP) Software

24" Flat Panel Monitors **Custom Paint**

Entry/Exit Roller Tables Environmental Kit

Footmat Operator Interlock

Heavy Duty Casters Long Conveyor

Radiation Meter

Remote Workstation Configuration











ISO 9001: Certified

¹Weight and dimensions of the system may vary depending on customization.

²As tested on Astrophysics Inc. Test Piece.

³Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information.

Due to continued product research and development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice.

Astrophysics HQ +1.909.598.5488

Astrophysics - DC +1.202.350.9740

Astrophysics - HOUSTON +1.713.357.5132

Astrophysics - EMEA +961.9.832.500/1/2

Astrophysics - INDIA +91.11.41709990

Astrophysics - ASIA +63.2.546.1741